



2241 Park Place, Suite B
Minden, NV 89423
(888) 782-8324
www.CHEMEON.com

Technical Data Sheet • CHEMEON® Chemical 6101

Description:

Mid-temperature seal surfactant package that helps eliminate smut. This product should be used with CHEMEON® Seal 6100.

Operating Conditions:

Method of Application:	Immersion
Concentration:	0.1-0.3 % by volume
pH:	5.5 – 6.5
Temperature	160 – 190 °F (70 – 90 °C)
Time.	1 - 10 minutes

Solution Control:

If smut appears on parts, add 0.1 % by volume of CHEMEON® Chemical 6101 to the CHEMEON® Seal 6100 solution.

Physical and Safety Data:

CHEMEON® Chemical 6101 is a neutral clear brown liquid.
CHEMEON® Chemical 6101 is not hazardous, but may be slightly irritating to skin or eyes.
In case of contact flush with water.

Packaging:

55 gallon drum

Storage:

Store CHEMEON® Chemical 6101 at ambient temperature in a dry place. Keep lid closed when not in use.

Waste Disposal:

Dispose of according to Federal, State, and local waste treatment regulations.

The information presented regarding this, or any other product manufactured or supplied by CHEMEON, is offered for your consideration, investigation and verification. Information presented is based on our own data and observations, or other sources believed to be reliable. CHEMEON shall have no liability with respect to any recommendations, instructions, or performance. CHEMEON's sole and exclusive warranty is that its products comply with CHEMEON's published chemical or physical specifications. CHEMEON makes no other warranties, either express or implied with respect to its recommendations, instructions, products, apparatus, process or otherwise, and specifically disclaims any implied warranties or merchantability, suitability, fitness for a particular purpose or otherwise. CHEMEON® Surface Technology LLC