



2241 Park Place, Suite B
Minden, NV 89423
(888) 782-8324
www.CHEMEONcom

Technical Data Sheet

CHEMEON[®] Liquid MBL Dye

Description:

CHEMEON (formerly Metalast) offers a full range of organic dyes for anodized aluminum.

Operating Conditions:

| | |
|------------------------|---|
| Method of Application: | Immersion |
| Concentration: | 10-15 g/L, may vary with application |
| Immersion Time: | 5 - 20 minutes depending on desired color |
| Temperature: | 120°F – 170°F (50°C – 77°C) |
| pH: | 5.0-5.5 |
| Water: | Use low hardness or deionized water |
| Tank: | Stainless steel plastic and fiberglass |

Recommendations For Make-Up and Maintenance:

- Deionized water or high quality tap water should be used for make-up
- Mix thoroughly before use

Physical and Safety Data:

CHEMEON Liquid MBL is a black liquid. If contact occurs, flush affected area with water for 15 minutes, if irritation persists, see a physician.

Packaging:

5 to 100 pound containers

The information presented regarding this, or any other product manufactured or supplied by CHEMEON, is offered for your consideration, investigation and verification. Information presented is based on our own data and observations, or other sources believed to be reliable. CHEMEON shall have no liability with respect to any recommendations, instructions, or performance. CHEMEON's sole and exclusive warranty is that its products comply with CHEMEON's published chemical or physical specifications. CHEMEON makes no other warranties, either express or implied with respect to its recommendations, instructions, products, apparatus, process or otherwise, and specifically disclaims any implied warranties or merchantability, suitability, fitness for a particular purpose or otherwise. CHEMEON[®] Surface Technology LLC