



2241 Park Place, Suite B  
Minden, NV 89423  
(888) 782-8324  
www.CHEMEON.com

## Technical Data Sheet

### CHEMEON® Gray NL

#### Description:

Gray dye for anodized aluminum. Lightfastness rating of 6-7. Does not leach. Black liquid.

#### Use Directions:

Methods of Application	Immersion
Concentration	3-5 g/l
Temperature	80-90° F*
Time.	5-20 minutes
pH.	6.0-6.5
Equipment.	Stainless steel, plastic and fiberglass

\*Do not exceed 90°F or color may shift

#### Physical & Safety Data:

CHEMEON Gray NL is a black liquid. If contact occurs, flush the affected area with water for 15 minutes, if irritation persists, see a physician.

#### Packaging:

5 to 100 lb containers

*The information presented regarding this, or any other product manufactured or supplied by CHEMEON, is offered for your consideration, investigation and verification. Information presented is based on our own data and observations, or other sources believed to be reliable. CHEMEON shall have no liability with respect to any recommendations, instructions, or performance. CHEMEON's sole and exclusive warranty is that its products comply with CHEMEON's published chemical or physical specifications. CHEMEON makes no other warranties, either express or implied with respect to its recommendations, instructions, products, apparatus, process or otherwise, and specifically disclaims any implied warranties or merchantability, suitability, fitness for a particular purpose or otherwise. CHEMEON® Surface Technology LLC*