



2241 Park Place, Suite B
Minden, NV 89423
(888) 782-8324
www.CHEMEON.com

Technical Data Sheet

CHEMEON® Gray N Dye

Description:

Aluminum anodizing dye that gives gray color. The product has a light fastness rating of 5 and has very low leaching.

Operating Conditions:

Method of Application:	Immersion, wipe
Concentration:	0.5-2.0 g/L
Immersion Time:	5-20 minutes
Temperature:	120°F – 150°F
pH:	7.5-8.5
Tank:	Stainless steel plastic and fiberglass

Physical and Safety Data:

CHEMEON Gray N Dye is a black powder. If contact occurs, flush affected area with water for 15 minutes, if irritation persists, see a doctor.

Packaging:

5 to 100 pound containers

The information presented regarding this, or any other product manufactured or supplied by CHEMEON, is offered for your consideration, investigation and verification. Information presented is based on our own data and observations, or other sources believed to be reliable. CHEMEON shall have no liability with respect to any recommendations, instructions, or performance. CHEMEON's sole and exclusive warranty is that its products comply with CHEMEON's published chemical or physical specifications. CHEMEON makes no other warranties, either express or implied with respect to its recommendations, instructions, products, apparatus, process or otherwise, and specifically disclaims any implied warranties or merchantability, suitability, fitness for a particular purpose or otherwise. CHEMEON® Surface Technology LLC